

Corning® Lambda™ EliteTouch™ Pipettors

Effortless pipetting and reliable results

End of the year offer for Corning® Lambda™ EliteTouch™ Pipettors!

Single-Channel
1 575 SEK/NOK
1 120 DKK
150 EUR

8-Channel
3 830 SEK/NOK
2 718 DKK
364 EUR

12-Channel
4 170 SEK/NOK
2 961 DKK
397 EUR



Corning Lambda EliteTouch pipettors have been engineered to provide the highest levels of ergonomics, accuracy, and precision. The lightweight construction, contoured handle, and 4-digit counter were designed to ensure comfortable pipetting. All pipettors feature smooth plunger movement and extremely low pipetting forces to reduce wrist strain and fatigue (RSI). Colored pushbuttons (included) can help identify a user or application for sample safety and lower risk of cross-contamination.

- ▶ Ergonomic handle design is a perfect fit for both the right and left hand
- ▶ Convenient one-hand volume setting with auto-lock system prevents accidental volume change during work
- ▶ 4-digit counter provides greater precision and is perfectly positioned for visibility at all times
- ▶ Single-channel pipettors are compatible with very narrow tubes
- ▶ Fully autoclavable and UV-resistant for sample protection against contaminations
- ▶ The multi-channel shafts retract individually for perfect tip loading and easier tip ejection
- ▶ Unique ejector lever system enables effortless tip ejection
- ▶ Easy in-lab calibration helps you quickly adjust your pipettor to various liquid types
- ▶ Individually tested and supplied with a certificate of quality

Ordering Information

Corning® Lambda™ EliteTouch™ Pipettors

Single-channel

Cat. No.	Volume Range (μL)	Accuracy (%)	Precision (%)	Tip (μL)	Qty/Cs
6050	0.1 - 2	±40.0 to ±1.5	≤12.0 to ≤0.7	10	1
6051	0.5 - 10	±4.0 to ±1.0	≤2.8 to ≤0.4	10	1
6052	2 - 20	±3.5 to ±0.8	≤1.5 to ≤0.3	200	1
6053	5 - 50	±3.5 to ±0.8	≤1.3 to ≤0.3	200	1
6054	10 - 100	±3.0 to ±0.8	≤1.0 to ≤0.2	200	1
6055	20 - 200	±2.0 to ±0.6	≤0.7 to ≤0.2	200	1
6056	100 - 1000	±2.5 to ±0.6	≤0.6 to ≤0.2	1000	1

8-channel

6057	0.5 - 10	±10.0 to ±2.0	≤8.0 to ≤1.2	10	1
6058	5 - 50	±4.0 to ±1.6	≤2.5 to ≤0.6	200	1
6059	20 - 200	±3.0 to ±1.0	≤1.5 to ≤0.6	200	1
6060	30 - 300	±3.0 to ±1.0	≤1.5 to ≤0.6	300	1

12-channel

6061	0.5 - 10	±10.0 to ±2.0	≤8.0 to ≤1.2	10	1
6062	5 - 50	±4.0 to ±1.6	≤2.5 to ≤0.6	200	1
6063	20 - 200	±3.0 to ±1.0	≤1.5 to ≤0.6	200	1
6064	30 - 300	±3.0 to ±1.0	≤1.5 to ≤0.6	300	1

Accessories

4088	Pipettor stand for one single-channel, 8-channel, or 12-channel pipettor	1
6066	Universal linear stand for four pipettors, orange (four single-channel, maximum of two 8-channel or 12-channel pipettors)	1
6067	Universal linear stand for four pipettors, transparent (four single-channel, maximum of two 8-channel or 12-channel pipettors)	1
6068	Universal linear stand for six pipettors, transparent (six single-channel, maximum of three 8-channel or 12-channel pipettors)	1

Warranty/Disclaimer: Unless otherwise specified, all products are for research use only. Not intended for use in diagnostic or therapeutic procedures. Corning Life Sciences makes no claims regarding the performance of these products for clinical or diagnostic applications.

The offer is valid until 2022-12-31

SAVEEN WERNER



SWEDEN

+46 40 51 00 0
www.swab.se
info@swab.se



NORWAY

+47 22 22 87 8
www.swab.no
info@swab.no



DENMARK

+45 86 20 16 1
www.swab.dk
info@swab.dk



FINLAND

+358 9 3154 5620
www.swab.fi
info@swab.fi